












Daily Disposables

Reusable Disposables

ACUVUE® Brand Contact Lenses	ACUVUE® OASYS 1-DAY with Hydraluxe™ Technology	ACUVUE® OASYS 1-DAY for Astigmatism	1-DAY ACUVUE® MOIST®	1-DAY ACUVUE® MOIST® Brand MULTIFOCAL	1-DAY ACUVUE® MOIST® for ASTIGMATISM	1-DAY ACUVUE® DEFINE®	ACUVUE® OASYS with Transitions™	ACUVUE® OASYS with HYDRACLEAR® Plus	ACUVUE® OASYS for ASTIGMATISM	ACUVUE® VITA™	ACUVUE® VITA™ for Astigmatism
	1 day						2 weeks			1 month	
Replacement	1 day						2 weeks			1 month	
Key Selling Point	 Provides exceptional comfort and helps minimize feelings of eye tiredness	 Sharp and stable vision with exceptional comfort	 Exceptional comfort for eyes prone to irritation	 Look and be sharper than ever for people with presbyopia	 All day long comfort and visual acuity for patients with Astigmatism	 Discover your natural eye radiance	 The Contact Lens That Knows Light™	 Exceptional comfort and performance in challenging environments	 Excellent comfort and visual acuity for patients with Astigmatism	 Providing a Full Month of Hydration	 Providing a Full Month of Hydration, Sharp and Stable Vision
Retail Price/ Box	\$72	\$78	\$56	\$88	\$67	\$67	\$88	\$56	\$67	\$66	\$128

Lens Properties

Lens Material	senofilcon A			etafilcon A			senofilcon A			senofilcon C		
Oxygen Flux (Open Eye)	98%			88%			98%					
Center Thickness @ -3.00D (mm)	0.085	0.080	0.084	Varies with power		0.090	0.084	0.085	0.070	0.080	0.070	0.080
UV Blocking	>99% UVB, >96% UVA			97% UVB 82% UVA			100% UVB >99% UVA		>99% UVB, >96% UVA			
Visibility Tint	Yes						Yes					
Inside-Out Mark	Yes ("123")	No (Scribes at 6 & 12 o'clock)	Yes ("123")		No (Scribes at 6 & 12 o'clock)	No	Yes ("123")	Yes ("123")	No (Scribes at 6 & 12 o'clock)	Yes ("123")	No (Scribes at 6 & 12 o'clock)	

Lens Specification

Lens Parameter	8.5 & 9.0 / 14.3	8.5 / 14.3	8.5 & 9.0 / 14.2	8.4 / 14.3	8.5 / 14.5	8.5 / 14.2	8.4 & 8.8 / 14.0	8.4 & 8.8 / 14.0	8.6 / 14.5	8.4 & 8.8 / 14.0	8.6 / 14.5
Full Power Range	-0.50 to -12.00 +0.50 to +8.00	Plano to -9.00 +0.25 to +4.00	-0.50 to -12.00 +0.50 to +6.00	Plano to -9.00 +0.25 to +6.00	Plano to -9.00 +0.25 to +4.00	Plano to -9.00 (no -0.25)	Plano to -12.00 +0.25 to +8.00	-0.50 to -12.00 +0.50 to +8.00	Plano to -9.00 +0.25 to +6.00	-0.50 to -12.00 +0.50 to +8.00	Plano to -9.00 +0.25 to +4.00

Low to Mid Minus

Sph (in 0.25 steps)	-0.50D to -6.00D		-0.50D to -6.00D		Plano to -6.00D		-0.50D to -6.00D		-0.50D to -6.00D		Plano to -6.00D	
Cyl & Axis	Cyl: -0.75D, -1.25D, -1.75D Axis: 10° to 180° in 10° steps		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 120°, 160°, 170°, 180°		Cyl: -2.25D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 120°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D Axis: 10° to 180° in 10° steps		Cyl: -2.25D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
Add			LOW +1.25D (+0.75D to +1.25D) MID +1.75D (+1.50D to +1.75D) HIGH +2.50D (+2.00D to +2.50D)									

High Minus

Sph (in 0.25 steps)	-6.25D to -9.00D									
Sph (in 0.50 steps)	-6.50D to -12.00D	-6.50D to -9.00D	-6.50D to -12.00D	-6.50D to -9.00D		-6.50D to -12.00D	-6.50D to -12.00D	-6.50D to -9.00D	-6.50D to -12.00D	-6.50D to -9.00D
Cyl & Axis	Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° in 10° steps		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
Add			LOW +1.25D (+0.75D to +1.25D) MID +1.75D (+1.50D to +1.75D) HIGH +2.50D (+2.00D to +2.50D)							

Plus Power

Sph (in 0.25 steps)	+0.50D to +6.00D	+0.25D to +4.00D	+0.50D to +6.00D	+0.25D to +6.00D	+0.25D to +4.00D	+0.25D to +6.00D	+0.50D to +6.00D	+0.25D to +6.00D	+0.50D to +6.00D	+0.25D to +4.00D
Sph (in 0.50 steps)	+6.50D to +8.00D		+6.50D to +8.00D		+6.50D to +8.00D		+6.50D to +8.00D		+6.50D to +8.00D	
Cyl & Axis	Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° in 10° steps		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
Add			LOW +1.25D (+0.75D to +1.25D) MID +1.75D (+1.50D to +1.75D) HIGH +2.50D (+2.00D to +2.50D)							

Amended on 29th May 2019

* Based on assumed usage. Number of boxes needed vary according to actual usage.
 ** Oxygen transmissibility at the center of -3.00D lens using boundary corrected, edge corrected DK value.
 *** 3 weeks to indent if product is out-of-stock / for oblique axis.
 † In accordance with American National Standards Institute (ANSI) and International Organization of Standardization (ISO) published standards of UV-protection.
 †† Help protect against transmission of harmful UV radiation to the cornea and into the eye. WARNING: UV-blocking contact lenses are not substitutes for protective UV-blocking eyewear. Long-term exposure to UV radiation is one of the risk factors associated with cataracts. Exposure is based on a number of factors such as environmental conditions (altitude, geography, cloud cover) and personal factors (extent and nature of outdoor activities). UV-blocking contact lenses help provide protection against harmful UV radiation. However, clinical studies have not been done to demonstrate that wearing UV-blocking contact lenses reduces the risk of developing cataracts or other eye disorders. Consult your eye care practitioner for more information. Disposable contact lenses are medical devices and patients are subjected to an eye examination with consultation fees. Johnson & Johnson Vision (Singapore) reserves the right to change any terms and conditions herein at any time without prior notice.
 ACUVUE® OASYS, Hydraluxe™, MOIST®, DEFINE®, Natural Shine™, Radiant Bright™, Radiant Charm™, Radiant Sweet™, LACREON™, HYDRACLEAR®, Intusight™, VITA™ and OASYS with Transitions™ are trademarks of Johnson & Johnson Vision ©. Johnson & Johnson Pte. Ltd. 2019.SG495

Johnson & Johnson Customer Service

Phone: 1800 896 3233
 Email: csr@its.jnj.com
 Fax: 1800 861 7307
 Time: Mon-Fri 9am - 7.30pm; Sun 11am-4pm

Minimum order for delivery: 2 boxes for all brands of ACUVUE™

*This is only a digital copy, NOT a Final Production.

Approval may be given in writing, committed to print from email or mobile text message, pixeltech will not be held responsible for any changes or amendment made after the approval. It is the sole responsibility of the client to notify pixeltech of any such errors during the revision cycle and before the final files have been generated.

In the event of a need to reprint due to errors in content, the cost of re-prints will be bear by client.

CHECK & APPROVED
核対后请签名

Signed

Date



(mm)
210w x 297h